



DAZZLER™ WB45-2000-3700

Wide Band-cut 45mm DAZZLER™

Specifications

PROGRAMMABLE AMPLITUDE AND PHASE FILTER
FOR FEMTOSECOND LASER PULSE SHAPING

- ✓ Ultra-compact device
- ✓ In-line geometry
- ✓ Advanced software functionalities
- ✓ Simple optical alignment

• Wavelength tuning range	2000 nm to 3700 nm
○ Wavelengths outside this range are poorly or not diffracted	
• Instantaneous bandwidth	up to 1700 nm
• Spectral resolution	3.5 nm at 2500 nm 7 nm at 3500 nm
• Intensity control dynamic range	> 45 dB
• Maximum programmable delay	5.5 ps at 2800 nm
• Diffraction efficiency for operation up to 7.5 kHz	50% on a 200 nm bandwidth 25% on a 400 nm bandwidth 35% on a 400 nm bandwidth 50% on a 600 nm bandwidth
○ With optional 20W RF amplifier (up to 4.5kHz)	
○ With optional 50W external RF amplifier (up to 2kHz)	
• Typical acoustic waveform refreshing time	< 3ms
• Input beam requirements	30 μJ max on $\phi = 2.5$ mm, collimated
• Optical module dimensions	48 x 98 x 22 mm ³
• Typical optical jitter	< 10 fs
○ With optional Low-jitter electronics	< 100 as

✓ Special feature for CEP control

Multi-kHz rate CEP control with the optional CEP modulation solution. This additional hardware allows dispersion-free, single-shot control of the CEP value down to 6mrad resolution.

